



## Technical data Luxura V<sub>10</sub>

### Available colours:

Royal Red  
Pearl White in de varianten:  
Passion, Romance, Cool

• = Standard ◦ = Optional

\*= Intensive-variant with 180 W tubes with long spot  
and 800 h recommended lifetime

Type →	50 XL	50 XL High Intensive*	50 XL IP Control	50 XLc	50 XLc High Intensive*	50 SLI	50 SLI High Intensive*
Tubes	50 x 120 W	50 x 180 W	50 x IP Control	50 x 120 W	50 x 180 W	42 x 120 W 8 x 80 W	42 x 180 W 8 x 140 W
Face tanner	-	-	-	Integrated	Integrated	4 x 400 W	4 x 400 W
SPS	-	-	-	-	-	•	•
HPS	-	-	-	-	-	◦	◦
Surface	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic	Metallic
Floor lighting	•	•	•	•	•	•	•
DecoLight	•	•	•	•	•	•	•
Stand-by	•	•	•	•	•	•	•
inside lighting	•	•	•	•	•	•	•
2Doors open synchronous	•	•	•	•	•	•	•
Digital timer display	•	•	•	•	•	•	•
Internal timer	•	•	•	•	•	•	•
Connection for external timer	•	•	•	•	•	•	•
Adjustable bodycooler: 1-2	•	•	•	•	•	•	•
Lift system	◦	◦	◦	◦	◦	◦	◦
Qsens (4 nozzles)	◦	◦	◦	◦	◦	◦	◦
Xsens	◦	◦	◦	◦	◦	◦	◦
Loudspeakers	•	•	•	•	•	•	•
SoundAround	◦	◦	◦	◦	◦	◦	◦
My MP3	◦	◦	◦	◦	◦	◦	◦
SmartVoice	◦	◦	◦	◦	◦	◦	◦
Hour-counter non-resetable	•	•	•	•	•	•	•
Hour-counter resetable	•	•	•	•	•	•	•
Connection	400 V/3N ~/PE/50Hz	400 V/3N ~/PE/50Hz	400 V/3N ~/PE/50Hz	400 V/3N ~/PE/50Hz	400 V/3N ~/PE/50Hz	400 V/3N ~/PE/50Hz	400 V/3N ~/PE/50Hz
Power	6,8kW	11,5kW	11,5kW	6,8kW	11,5kW	8,5kW	13kW
Fuses	3 x 16 A	3 x 20 A	3 x 16 A	3 x 16 A	3 x 20 A	3 x 20 A	3 x 25 A
Weight (excl. Packaging)	600 kg	650 kg	500 kg	600 kg	650 kg	625 kg	675 kg